

PLUMBING

Hoses and fillers.....	146
Tanks and accessories	149
Pumps.....	152
Plumbing fittings	157
Hot water heaters.....	162
Filtration.....	164
Sinks and basins.....	165
Tapware	168
Bathroom accessories	173
Bathroom modules.....	174
Gas compliance and safety.....	175
Gas fittings and adaptors.....	178
Gas cylinders and accessories.....	179
Gas regulators and hoses	186



GAS COMPLIANCE AND SAFETY



GAS DETECTOR SAFE-T-ALERT 12V
000342

Gas detector Safe-T-Alert 12V suitable for LPG and natural gas.

FEATURES:

- Draws 46 MA and is simple to operate
- When the test switch is activated a complete diagnostic test is performed
- The detector is fully operational from 6 to 16V DC, providing continuous operation
- Required 12V permanent connection



METAL GAS INSTRUCTION PLATE (MARINE)
003870

Metal gas instruction plate with consumer instructions for fixing to marine craft.

SPECIFICATIONS:

- Dimensions: 100mm(l) x 90mm(h) x 2mm(d)
- Pack of 2 different pieces



LPG CONSUMER INSTRUCTION PLATES (CARAVAN)
003869

Metal gas instruction plate with consumer instructions for fixing to caravans

SPECIFICATIONS:

- Dimensions: 100mm(l) x 100mm(h) x 1mm(d)
- Pack of 2 different pieces

This vent must remain unrestricted to provide ventilation when LP Gas appliances are in use

GAS VENT VENTILATION DECAL
043380

White with black writing.

WARNING
Ensure ventilation when the
Cooker is in use.
Do not use for space heating.

GAS VENTILATION DECAL
043381

White with black writing.



GAS COMPLIANCE DECAL

- 003875 NO. 3 - NEAR STOVE
- 003877 NO. 5 - BOOT LID
- 003878 NO. 6 - EVACUATION

Consumer instructions for fixing to caravans/ marine craft.



GAS TEST POINT 3/8IN
003910

This test point is located immediately downstream from the regulator. It allows the user to easily test that gas is coming through the regulator and that it is at reduced pressure.

FEATURES:

- May be used with flared nut ID-601 for 3/8" pipe

SPECIFICATIONS:

- Inlet is from regulator - 3/8" male BSP
- Outlet is 3/8" SAE male flare



GAS PRESSURE TEST POINT
003909

This test point is located immediately downstream from the regulator. It allows the user to easily test that gas is coming through the regulator and that it is at reduced pressure.

SPECIFICATIONS:

- 5/16" SAE Male x 3/8" BSPT Male
- Inlet: 3/8" - screws into regulator
- Outlet: 5/16" SAE Male flare



CHROME FLOOR MOUNT X 1/2" FEMALE BSP
004051

To suit low pressure appliances such as barbecues and flueless space heaters. For floor or wall mount.

FEATURES:

- Chrome plated
- Dust cap
- Mounting screws x 2

SPECIFICATIONS:

- Connection: 1/2" female
- Maximum Inlet Pressure: 7kPa
- Chrome



COPPER TUBE

- 003950 1/4" 50M ROLL
- 003952 5/16" 30M ROLL
- 003954 3/8" 18M ROLL

Annealed copper tube suitable for gas installations.



YELLOW 12MM THREAD SEAL GAS TAPE (10M)

004063

Used on threaded joins on gas pipe.

- Yellow



NO 6 FLARE NUT AE

- 003966 - 1/4" MALE SAE
- 003967 - 5/16" MALE SAE
- 003968 - 3/8" MALE SAE
- 003970 - 1/2" FEMALE SAE
- 003973 - RED 3/8" FEMALE SAE X 5/16" TUBE
- 003974 - RED 1/2" FEMALE SAE X 3/8" TUBE

Flare nuts are placed over the copper pipe prior to using the FLARE tool.



SADDLES

Used to secure copper tube to the chassis.

COPPER

- 003959 - 5/16" - 7.95MM TUBE
- 003960 - 3/8" - 9.52MM TUBE
- 003961 - 1/2" - 12.7MM TUBE

PLASTIC

- 042642 - 13MM
- 042656 - 19MM



BALL VALVES

- 004043 - 1/4"FBSP X 1/4"FBSP
- 004046 - 5/16"SAE AND NUTS
- 004047 - 3/8"BSPT AND NUTS
- 004048 - 3/8"SAE AND NUTS



COMPANION FEMALE 3/8" LEFT HAND THREAD X FEMALE POL

004054



GF5 ADAPTOR GAS FITTING
050044

GF5 adaptor gas fitting adaptor 1/4 BSPF x 3/8 male sae for BBQ and ring burners.

Note: BSP fittings require thread tape. Always test for leaks after working on any gas fittings.

GAS FITTINGS AND ADAPTORS



ELBOW 3/8" LEFT HAND THREAD
004056 - 3/8" MBSP X POL MALE LH R ANGLE
004059 - 3/8" FLH BSP X FEMALE POL



NO 8 ELBOW
003992 - 3/8" MALE SAE X 1/4" MALE BSP
003989 - 5/16" MALE SAE X 1/4" MALE BSP
003990 - 5/16" MALE SAE X 3/8" MALE BSP



NO 25 EXTRUDED ELBOW
036532 - 3/8" MALE BSP X 3/8" FEMALE BSP
004018 - 1/4" MALE BSP X 1/4" FEMALE BSP

NO 38 SINGLE UNION BODY
036542 - 5/16" MALE BSP X 1/8" MALE BSP
036544 - N5/16" MALE SAE X 3/8" MALE SAE
036543 - 5/16" MALE SAE X 1/4" MALE SAE
036546 5/16 X 3/8 M/F



NO 56 FLARE CAP NUT
004029 - 5/16" FEMALE FLARE SAE



NO 72 ADAPTOR
036553 - 3/8" FEMALE BSP X 1/4" MALE BSP
036552 - 1/4" FEMALE BSP X 1/4" MALE BSP
036554 - 1/2" FEMALE BSP X 1/4" MALE BSP
036555 - 1/2" FEMALE BSP X 3/8" MALE BSP



NO 16 FEMALE UNION
004001 3/8" MALE SAE X 3/8" FEMALE BSP
004000 3/8" MALE SAE X 1/4" FEMALE BSP
004002 3/8" MALE SAE X 1/2" FEMALE BSP
003995 1/4" MALE SAE X 1/4" FEMALE BSP
004003 1/2" MALE SAE X 3/8" FEMALE BSP
003997 5/16" MALE SAE X 1/4" FEMALE BSP



NO 17 DOUBLE UNION
004004 - 1/4" MALE SAE X 1/4" MALE SAE
004006 - 3/8" MALE SAE X 3/8" MALE SAE
004005 - 5/16" MALE SAE X 5/16" MALE SAE
004007 - 5/16" MALE SAE X 1/4" MALE SAE



NO 27 HEXAGON NIPPLE 1/4" X 1/4"
004020 - 1/4" MALE BSP X 1/4" MALE BSP



NO 62 - 1/4" MALE BSP X 1/4" FEMALE UNION
004033

Used to convert copper pigtailed with dual/changeover regulators. For use with single OPP regulators less POL.

SPECIFICATIONS:

- Female Union 1/4" Male BSPT Inverted Flare 1/4"



NO 65 FLARE PLUG
004035 - 5/16" FEMALE FLARE SAE
004036 - 3/8" MALE SAE



NO 73 REDUCING NIPPLE
004041 - 3/8" MALE BSP X 1/4" MALE BSP
036556 - 1/4" X 1/8"



NO 7 UNION
003981 3/8" MALE SAE X 1/8" MALE BSP
003983 3/8" MALE SAE X 3/8" MALE BSP
003982 3/8" MALE SAE X 1/4" MALE BSP
003984 3/8" MALE SAE X 1/2" MALE BSP
003976 1/4" MALE SAE X 3/8" MALE BSP
003977 5/16" MALE SAE X 1/8" MALE BSP
003979 5/16" MALE SAE X 3/8" MALE BSP
003980 5/16" MALE SAE X 1/2" MALE BSP



NO 24 REDUCING BUSH
036529 - 3/8" FEMALE BSP X 1/4" MALE BSP
036530 - 1/2" FEMALE BSP X 1/4" MALE BSP
036531 - 1/2" FEMALE BSP X 3/8" MALE BSP



NO 36 FEMALE UNION ELBOW
004028 - 3/8" MALE SAE X 3/8" FEMALE BSP
036541 - 5/16" MALE SAE X 1/4" FEMALE BSP



NO 39 DOUBLE UNION BODY
036547 5/16" X 5/16IN



NO 70 FLARE SWIVEL
004038 - 3/8" FEMALE SAE X 3/8" FEMALE SAE
004037 - 5/16" FEMALE SAE X 5/16" FEMALE SAE



GAS ADAPTOR 1/2" MALE BSP X 5/16" SAE MALE FLARE
042580

Note: BSP fittings require thread tape. Always test for leaks after working on any gas fittings.



ADAPTOR STRAIGHT 3/8" LEFT HAND
035715

Adaptors to suit 3/8" BSP left hand cylinders.

SPECIFICATIONS:

- 3/8" left hand Male x 1/4" Female BSP



GAS CYLINDER VALVE SAFETY PLUG ONLY POL
036513

Prevents accidental leaks and hazards during transportation of cylinder or when not in use.



GF12 ADAPTOR GAS FITTING
050045

Quick action connect 3/8 SAEF x 3/8 SAEM QC80



ADAPTOR MALE POL TO 1/4" MALE BSP
035719

Adaptors to suit POL cylinders.

SPECIFICATIONS:

- Male POL to 1/4" Male BSP



ADAPTOR 9KG BOTTOM TO 3/8" LEFT HAND COMPANION
035722

Adaptor that fits into a 4.5 or 9kg gas bottle and allows 3/8 left hand thread to connect.



NO 18 DOUBLE ELBOW

004011 - 3/8" MALE SAE X 3/8" MALE SAE

004010 - 5/16" MALE SAE X 5/16" MALE SAE



MALE BAYONET FITTING

033800

Low pressure appliance hose adaptor.

FEATURES:

- Dust cap
- Brass



ADAPTOR 3/8" LEFT HAND FEMALE TO 1/4" BSP MALE

035714

Adaptors to suit 3/8" BSP left hand cylinders.



GAS BAYONET DUST CAP

043382



NO 19 3-WAY

004014 - NO19 3-WAY TEE 3/8 SAE

004013 - NO19 3-WAY TEE 5/16 SAE

GAS HOSE PVC

036512	300MM	1/4" F INV FLARE BSP X 1/4" F INV FLARE BSP
003944	600MM	1/4" F INV FLARE BSP X 1/4" F INV FLARE BSP
036509	1800MM	1/4" F INV FLARE BSP X 1/4" F INV FLARE BSP
036508	2400MM	1/4" F INV FLARE BSP X 1/4" F INV FLARE BSP
003920	600MM	3/8" F FLARE SAE X 3/8" F FLARE SAE
003924	1200MM	3/8" F FLARE SAE X 3/8" F FLARE SAE
003919	1800MM	3/8" MALE BSP X 3/8" F FLARE SAE
036510	900MM	3/8" MALE BSP X 1/4" F BSP INV FLARE
003935	1200MM	3/8" MALE BSP X 1/4" F BSP INV FLARE



CODE 003930

003937	1500MM	3/8" MALE BSP X 1/4" F BSP INV FLARE
003911	300MM	3/8" MALE FLARE SAE X 3/8" MALE BSP
003912	450MM	3/8" MALE FLARE SAE X 3/8" MALE BSP
003913	600MM	3/8" MALE FLARE SAE X 3/8" MALE BSP
003927	300MM	5/16" MALE FLARE SAE X 3/8" MALE BSP
003928	450MM	5/16" MALE FLARE SAE X 3/8" MALE BSP
003929	600MM	5/16" MALE FLARE SAE X 3/8" MALE BSP
003930	600MM	5/16" F FLARE SAE X 5/16" F FLARE SAE
003931	1200MM	5/16" F FLARE SAE X 5/16" F FLARE SAE



CODE 003927

SPECIFICATIONS:

- Maximum Working Pressure: 2600kPa
- Working Temperature Range: -20°C to +65°C



GAS FUSE SAFETY VALVE

044813

Gasfuse safety devices are available for LPG gas bottles and are ideal for household barbecues, patio heaters, caravans, boating and camping applications and are available in both POL and 3/8th fittings

Note: BSP fittings require thread tape. Always test for leaks after working on any gas fittings.

GAS CYLINDERS AND ACCESSORIES



GAS CYLINDERS

- 040408 - 9KG POL NO GAUGE CAMEC
- 003860 - 9KG GALV AND POL NO GAUGE
- 003852 - 4.5KG C/W POL-TALL
- 041778 - 4.5KG C/W POL-TALL
- 003853 - 4KG C/W POL-SQUAT
- 003861 - 4KG GALV AND POL NO GAUGE
- 003857- 2KG 3/8 L/H THREAD
- 003856 - 1.25KG 3/8 L/H THREAD

FEATURES:

- AGA approved
- Class 2 gas cylinders are specifically coated making them suitable for recreational vehicles, and general use



GAS DOOR FOR GALVANISED BOX (003830)

Available with left or right hand hinge in smooth or stucco white. Lockable - includes 2 keys.

- 003835 LHH SMW WHITE
- 003837 RHH SMW WHITE
- 003831 ILL



GAS BOX GALVANISED

003830

To suit 9kg gas cylinder. Mostly used in small motorhome conversions.

FEATURES:

- Prefabricated sealed compartment
- Lockable door available (not included)
- Gas cylinder not included

SPECIFICATIONS:

- Dimensions: 360mm(w) x 505mm(h) x 360mm(d)



GAS HOSE STAINLESS STEEL SINGLE REGULATOR FLEXIBLE PIGTAIL EXCESS FLOW

- 003906 450MM 1/4" MALE NPT X POL
- 038300 600MM 1/4" MALE NPT X POL

Replacement for PVC pigtail.

FEATURES:

- AGA approved

SPECIFICATIONS:

- 1/4" Male NPT
- Class C
- Maximum Working Pressure: 2600kPa
- Working Temperature Range: -20°C to +65°C



GAS HOSE STAINLESS STEEL DOUBLE REGULATOR EXCESS FLOW

- 003899 - 450MM 7/16" INV FLARE X POL

Replacement for copper pigtail.

FEATURES:

- AGA approved
- Flexible pigtail

SPECIFICATIONS:

- 450mm x 7/16" inverted flare
- Class C
- Maximum Working Pressure: 2600kPa
- Working Temperature Range: -20°C to +65°C



ADJUSTABLE FRONT OPENING SMALL GAS BOTTLE HOLDER

- 050030 - SMALL
- 050031 - LARGE

SMALL - Front opening suits 4kg gas bottle zinc plate weld on 1.38kg. To used with camper trailers and other situations where there is limited access.

LARGE - Front opening suits 9kg gas bottle zinc plate weld on 2kg. To used with camper trailers and other situations where there is limited access.



GAS HOSE 1200 BRAID X 5/16" MALE

003932

SPECIFICATIONS:

- Class C
- Maximum Working Pressure: 2600kPa
- Working Temperature Range: -20°C to +65°C



GAS HOSE STAINLESS STEEL SINGLE REGULATOR FLEXIBLE EXCESS FLOW

- 003905 - 450MM H/WHEEL 1/4" MALE NPT X H/WHEEL POL
- 036518- 600MM H/WHEEL 1/4" MALE NPT X H/WHEEL POL

Maximum Working Pressure: 2600kPa

- Working Temperature Range: -20°C to +65°C



GAS CYLINDER CRADLE UNIVERSAL, EXTRA STRONG BASE.

- 003829 - 9KG PLATED - ADJUSTABLE CLAMP
- 039073 - CRADLE

Note: BSP fittings require thread tape. Always test for leaks after working on any gas fittings.



MANUAL CHANGEOVER GAS VALVE
043464

Easily switch between cylinders. Replacement manifold for twin cylinder regulator set ups.



GAS DOUBLE REGULATOR AUTO AND COPPER PIGTAIL
003895

Adjustable LPG regulator, dual stage for RV installations.

FEATURES:

- Complete with copper pigtails (450mm) x 2, bracket and fixing screws

SPECIFICATIONS:

- Automatic changeover
- Capacity: 200mj/hr - 4kg/hr
- Inlet: 7/16" NPT
- Outlet: 3/8" NPT



GAS REGULATOR SINGLE-STRAIGHT POL
003884

036523 REPLACEMENT SOFT NOSE CONE

Straight adjustable soft nose regulator. Not for RV use

SPECIFICATIONS:

- Capacity: 175mj/hr - 3.5kg/hr
- Inlet: POL
- Outlet: 3/8" NPT



GAS BAYONET HOSE

- 002920 - 1.2M BAYONET X 1/4" BSPF
- 002914 - 1.5M BAYONET X 1/4" BSPF
- 002913 - 2.0M BAYONET X 1/4" BSPF

SPECIFICATIONS:

- Class B
- Maximum Working Pressure: 7 kPa
- Working Temperature Range: -20°C to +125°C



MARSHALL SINGLE REGULATOR OPP 190MJ

- 042050 190MJ
- 042051 290MJ

This two stage regulator combines both a high pressure first stage and a low pressure second stage regulator into a single unit. Ideal for RV applications to ensure a smooth and continuous flow.

SPECIFICATIONS:

- Inlet Pressure: 100psi
- Outlet Pressure: 9" W.C
- Inlet: 1/4" NPT FEM



SINGLE REGULATOR WITH OVER PRESSURE PROTECTION NO POL
6060521

036520

Non adjustable regulator for RV installations only.

FEATURES:

- Includes 1/4" inverted flare adaptor, bracket and fixing screws

SPECIFICATIONS:

- Capacity: 160mj/hr - 3.2kg/hr
- Inlet: 1/4" NPT
- Outlet: 3/8" NPT



PIGTAIL COPPER POL

036517 - 460MM (7/16" MALE INV FLAREF POL)

003897 - 762MM (30")

SPECIFICATIONS:

- Not suitable for single cylinder installations
- POL x 7/16" inverted flare suits most applications
- Class C
- Maximum Working Pressure: 2600kPa



GAS CYLINDER GAUGE ACCU-LEVEL MAGNETIC STRIP GAUGE
003868

FEATURES:

- To activate, pour hot water down the heat sensitive strip
- Reusable magnetic strip



GAS REGULATOR OPP MANUAL DUAL AND BRACKET
003892

Non adjustable regulator for RV installations only.

FEATURES:

- Dual stage
- Complete with bracket and fixing screws

SPECIFICATIONS:

- Manual changeover
- Capacity: 160mj/hr - 3.2kg/hr
- Inlet: 7/16" FNPT x 2
- Outlet: 3/8" NPT



REGULATOR AND HOSE KIT 1.8M
036519

Suitable for BBQs and gas camping fridges.

SPECIFICATIONS:

- Length: 1.8m x 8mm (diam)
- Capacity: 2kg/hr
- Hose type: PVC 8mm ID
- Inlet: POL
- Outlet: 1/4" BSPF



GAS HOSE STAINLESS STEEL DOUBLE REGULATOR EXCESS FLOW
003902

SPECIFICATIONS:

- 450mm x 7/16" inverted flare with hand wheel
- Class C
- Maximum Working Pressure: 2600kPa
- Working Temperature Range: -20°C to +65°C

Note: BSP fittings require thread tape. Always test for leaks after working on any gas fittings.